





SKIL





VWD

Remote

Stick

888

I

Lock

TIG

AMPS



Arc force



Hot start



Welding current

Buddy™

Arc 400i

+



-



ON/OFF POWER



AMPS



VOLT



READY



LOCK



WELDING CLASSIFY AIR



F-240



THROTTLE-UP  
WORK  
RELEASE-UP

**RS 400**  
Throttled IGBT Welding Power Source

NEGATIVE  
CLAMP

POSITIVE  
CLAMP

WELDING  
CONTROL





STAR MINI OVEN  
230 V A.C  
600 W 300°

The image shows a blue rectangular mini oven. The front door has a white rectangular label with a star logo at the top. Below the logo, the text reads 'STAR MINI OVEN', '230 V A.C', and '600 W 300°'. The oven has a silver handle on the right side of the door. At the bottom of the front panel, there is a red push-button on the left, a black rotary temperature dial in the center, and a green push-button on the right. The oven is sitting on a wooden surface in a workshop-like environment.









**TRANSWELD 400**

Output Power	4000 VA
Input Power	4000 VA
Output Current	20 A
Output Voltage	220 V
Output Frequency	50 Hz
Output Phase	Single Phase
Output Protection	Overload, Short Circuit
Output Regulation	±1%
Output Noise	≤65 dB
Output Efficiency	≥95%
Output THD	≤5%
Output Ripple	≤1%
Output Accuracy	±0.5%
Output Stability	±0.5%
Output Reliability	MTBF ≥ 100,000 h
Output Safety	CE, RoHS, ISO9001

TRANSWELD 400











ON

ON




OFF

**CUT-70**

CE

**mos**



DISCONNECT



M-400 AMPS.



STARTED

⊕  
VDC FEED

⊖  
VARS

HF UNIT

INDICATOR



START

BEATED



DC Welding Rectifier 400

Welding Chart

Material	Electrode	Current (A)	Speed (mm/min)
Stainless Steel	308	100-150	15-25
Aluminum	4043	100-150	15-25
Carbon Steel	6010	100-150	15-25
Cast Iron	6010	100-150	15-25
Brass	6010	100-150	15-25
Copper	6010	100-150	15-25
Aluminum	5356	100-150	15-25
Stainless Steel	309	100-150	15-25
Carbon Steel	6010	100-150	15-25
Cast Iron	6010	100-150	15-25
Brass	6010	100-150	15-25
Copper	6010	100-150	15-25

M.A. SYSTEMS



NEGATIVE

POSITIVE

WELDING LEAD

